



Installation Method



Quarter turn

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Meet **Color** 180770 Fog **Collection** First Option **Backing** GlasBac®

Product Specifications

Product Number	19DR302500
Product Construction	Tufted Textured Loop
Yarn System	100% Recycled Content Type 6 Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Dye Lots	Non-Mergeable
Soil/Stain Protection	Protekt®
Preservative Protection	Intersept®

	Imperial	Metric
Tufted Yarn Weight	14 oz/yd ²	475 g/m ²
Machine Gauge	1/12 in	47.2 ends/10cm
Pile Height	0.15 in	3.8 mm
Pile Thickness	0.099 in	2.5 mm
Stitches	9 /in	35.4 ends/10cm
Pile Density	5,091 oz/yd ³	188,773.1 g/m ³
Size	19.69 in x 19.69 in	50cm x 50cm

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Class 1
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC -134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.9 to 2.2
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

Environmental Specifications

Total Recycled Content	70%
Recycled Content (Post Industrial)	63%
Recycled Content (Post Consumer)	7%
Indoor Air Quality	Green Label Plus #GLP0820
Ingredients and Life Cycle Impacts	Environmental Product Declaration
Other Environmental Claims	3rd Party Verified Carbon Neutral NSF/ANSI 140 Gold - Sustainability Assessment
End of Life	Carpet to Carpet Recycling

Technical Information

Installation	See Interface Installation Guidelines online
Maintenance	See recommended Interface Maintenance Guidelines online
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard Carpet Warranty
Standard Backing	GlasBac®
Backing Options	GlasBac®, GlasBac®RE, CushionBac Renew™
Tile Size Options	50cm x 50cm
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States